Revision: 12 Revision date: 04/03/2015 Supersedes date: 02/04/2014 V11



SAFETY DATA SHEET **BRAKE & PARTS CLEANER**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **BRAKE & PARTS CLEANER**

Product number TBC025,BPC050,GFB050,PBC050,BPC025,TMX612,QHB005

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED

> Bury Lancashire England BL9 7NY

0161 764 5981 0161 797 5899 info@tetrosyl.com

Manufacturer TETROSYL LIMITED

> Bury Lancashire England BL9 7NY

0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

0161 764 5981 **Emergency telephone**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Asp. Tox. 1 - H304 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

1999/45/EC)

Classification (67/548/EEC or Xi;R38. F;R11. N;R51/53. R67.

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

2.2. Label elements

Pictogram









Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P261 Avoid breathing vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye and face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

Detergent labelling

aliphatic hydrocarbons, < 5% anionic surfactants

Supplementary precautionary statements

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS (<0.1% BENZENE CONTENT)

60-100%

CAS number: — EC number: 927-510-4

REACH registration number: 01-2119475515-33-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304

STOT SE 3 - H336

Aquatic Chronic 2 - H411

IPA 10-30%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC)

F;R11 Xi;R36 R67

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove affected person from source of contamination. Effects may be delayed. Keep

affected person under observation. Get medical attention. CAUTION! First aid personnel must be aware of own risk during rescue! Move affected person to fresh air at once. Keep affected person away from heat, sparks and flames. If breathing stops, provide artificial respiration. Place unconscious person on the side in the recovery position and ensure

breathing can take place.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel. Place unconscious person on their side in the recovery position and ensure breathing can

take place. If breathing stops, provide artificial respiration.

Ingestion Get medical attention immediately. Rinse mouth thoroughly with water. Give plenty of water to

drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. Never give anything by mouth to an unconscious person. Keep affected person away from heat, sparks and flames. Place unconscious person on their side in the

recovery position and ensure breathing can take place.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Rinse with

water. Use suitable lotion to moisturise skin. Get medical attention promptly if symptoms occur

after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any

discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

In case of overexposure, organic solvents may depress the central nervous system causing

dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache.

Fatigue. Dizziness. Central nervous system depression.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea,

headache, dizziness and intoxication. May cause chemical burns in mouth and throat. Central nervous system depression. Fumes from the stomach contents may be inhaled, resulting in

the same symptoms as inhalation.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Irritation, burning, lachrymation, blurred vision after liquid splash.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is highly flammable.

Hazardous combustion

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Risk of re-ignition after fire has been extinguished. Risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Containers close to fire should be removed or cooled with water.

Do not allow water to contact any leaked material.

Special protective equipment

for firefighters

Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Use suitable

respiratory protection if ventilation is inadequate. Take precautionary measures against static discharges. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe vapour. Avoid contact with skin and eyes. In case of spills, beware of slippery floors

and surfaces.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid the spillage or runoff

entering drains, sewers or watercourses. Avoid discharge to the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

For waste disposal, see Section 13. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Contact Health and Safety department on 6695 for further assistance.

6.4. Reference to other sections

Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Vapours may accumulate on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Good personal hygiene procedures should be implemented. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Mechanical ventilation or local exhaust ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Keep only in the original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures. Store away from the following materials: Oxidising materials.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

IPA

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³ WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment













Appropriate engineering controls

Use explosion-proof general and local exhaust ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is

required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate

the gloves. Frequent changes are recommended.

Other skin and body

protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures Provide eyewash station. Wash promptly with soap and water if skin becomes contaminated.

When using do not eat, drink or smoke. Contaminated clothing should be placed in a closed

container for disposal or decontamination.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Check that the

respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the

following cartridge: Gas filter, type AX.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Not entered.

Odour Solvent. Alcoholic.

Odour threshold Not determined. Scientifically unjustified. Not determined. Scientifically unjustified.

pH Not determined. Scientifically unjustified. Not determined. Scientifically unjustified.

Melting point Not determined. Scientifically unjustified.

Initial boiling point and range $~80^{\circ}\text{C}$ @

Flash point -12°C

Evaporation rate Not determined. Scientifically unjustified.

Upper/lower flammability or

explosive limits

Scientifically unjustified. Not determined.

Vapour pressureNot determined.Vapour densityNot determined.

Relative density 0.715 @ °C

Solubility(ies) Insoluble in water.

Partition coefficient Not determined. Scientifically unjustified.

Auto-ignition temperature Not determined. Scientifically unjustified.

Decomposition Temperature Not determined. Scientifically unjustified.

Viscosity <50 cP @ °C

Oxidising properties Not available.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Vapours may form explosive mixtures with air.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not relevant.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or

direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None at ambient temperatures. Oxides of carbon. Thermal decomposition or combustion may

liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems. The product contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous

vapour concentrations.

Inhalation Vapours may irritate throat/respiratory system. Symptoms following overexposure may include

the following: Headache. Dizziness. Drowsiness. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. The product contains organic solvents. Overexposure may depress the central nervous system, causing

dizziness and intoxication.

Ingestion May cause internal injury. May cause nausea, headache, dizziness and intoxication. Harmful:

may cause lung damage if swallowed. Pneumonia may be the result if vomited material

containing solvents reaches the lungs.

Skin contact Prolonged contact may cause dryness of the skin. Repeated exposure may cause skin

dryness or cracking.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain. Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

hazards

This chemical can be hazardous when inhaled and/or touched. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. May cause

severe internal injury. Vapour from this product may be hazardous by inhalation.

Route of entry Inhalation Ingestion. Skin and/or eye contact Skin absorption

Medical symptoms Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

Revision date: 04/03/2015 Revision: 12 Supersedes date: 02/04/2014 V11

BRAKE & PARTS CLEANER

Medical considerations Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis.

SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute toxicity - fish LC₅₀, 96 hours: >13.4 mg/l (Onchorhynchus mykiss) mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 3 mg/l (Daphnia magna) mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 10 mg/l (Raphidocelis) mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined. Scientifically unjustified.

12.4. Mobility in soil

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority. Do not puncture or

incinerate, even when empty.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations. Containers

should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion. Reuse or

recycle products wherever possible.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PROPAN-2-OL)

Proper shipping name

(IMDG)

FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PROPAN-2-OL)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PROPAN-2-OL)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PROPAN-2-OL)

14.3. Transport hazard class(es)

ADR/RID class

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group II

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

Emergency Action Code 3YE

Hazard Identification Number 33

(ADR/RID)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 04/03/2015

Revision 12

Supersedes date 02/04/2014 V11

SDS status Approved.

Risk phrases in full R11 Highly flammable.

R36 Irritating to eyes. R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.