

Page 1 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.10.2019 / 0019
Replacing version dated / version: 07.03.2017 / 0018
Valid from: 30.10.2019
PDF print date: 30.10.2019
Liquimate 8100 1K-PUR grau 300 mL
Art.: 6154

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Liquimate 8100 1K-PUR grau 300 mL
Art.: 6154

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive sealant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 1 - Adhesives, sealants

Process category [PROC]:

PROC 5 - Mixing or blending in batch processes

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC12 - Use of blowing agents in manufacture of foam

PROC13 - Treatment of articles by dipping and pouring

PROC14 - Tableting, compression, extrusion, pelletisation, granulation

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 2 - Formulation into mixture

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 5 - Use at industrial site leading to inclusion into/onto article

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.10.2019 / 0019
Replacing version dated / version: 07.03.2017 / 0018
Valid from: 30.10.2019
PDF print date: 30.10.2019
Liquimate 8100 1K-PUR grau 300 mL
Art.: 6154

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH204-Contains isocyanates. May produce an allergic reaction.
EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

| Reaction mass of ethylbenzene and xylene | Substance for which an EU exposure limit value applies. |
|---|--|
| Registration number (REACH) | 01-2119488216-32-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 905-588-0 (REACH-IT List-No.) |
| CAS | --- |
| content % | 1-<10 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332 Asp. Tox. 1, H304 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (organs of hearing) |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Page 3 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.10.2019 / 0019
Replacing version dated / version: 07.03.2017 / 0018
Valid from: 30.10.2019
PDF print date: 30.10.2019
Liquimate 8100 1K-PUR grau 300 mL
Art.: 6154

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Page 4 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

Ensure good ventilation.
 Avoid inhalation of the vapours.
 Keep away from sources of ignition - Do not smoke.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Protect against moisture and store closed.
 Protect from frost.
 Protect from direct sunlight and warming.
 Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Chemical Name | Reaction mass of ethylbenzene and xylene | Content %:1-<10 |
|---|---|-----------------|
| WEL-TWA: 220 mg/m3 (50 ppm) (WEL), 50 ppm (221 mg/m3) (EU) (Xylene), 100 ppm (441 mg/m3) (WEL), 100 ppm (442 mg/m3) (EU) (Ethylbenzene) | WEL-STEL: 100 ppm (441 mg/m3 (WEL), 100 ppm (442 mg/m3) (EU) (Xylene), 125 ppm (552 mg/m3) (WEL), 200 ppm (884 mg/m3) (EU) (Ethylbenzene) | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 54-1 (2004) MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004) | |
| BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV) (Xylene) | Other information: Sk (WEL) (Xylene), Sk (WEL) (Ethylbenzene) | |
| Chemical Name | Titanium dioxide | Content %: |
| WEL-TWA: 10 mg/m3 (total inhalable dust), 4 mg/m3 (respirable dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Poly vinyl chloride | Content %: |
| WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res. dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Diisononyl phthalate | Content %: |
| WEL-TWA: 5 mg/m3 | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Calcium carbonate | Content %: |
| WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |

Page 5 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

Reaction mass of ethylbenzene and xylene

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|------------------------------|------------|-------|------------|------|
| | Environment - freshwater | | PNEC | 0,327 | mg/l | |
| | Environment - marine | | PNEC | 0,327 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 6,58 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 12,46 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 12,46 | mg/kg dw | |
| | Environment - soil | | PNEC | 2,31 | mg/kg dw | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 12,5 | mg/kg bw/d | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 65,3 | mg/m3 | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 260 | mg/m3 | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 65,3 | mg/m3 | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 260 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 221 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 221 | mg/m3 | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 442 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 212 | mg/kg bw/d | |

Titanium dioxide

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|-----------------------------|------------|--------|------------|------|
| | Environment - freshwater | | PNEC | 0,184 | mg/l | |
| | Environment - marine | | PNEC | 0,0184 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 0,193 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 100 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 1000 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 100 | mg/kg dw | |
| | Environment - soil | | PNEC | 100 | mg/kg dw | |
| | Environment - oral (animal feed) | | PNEC | 1667 | mg/kg feed | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 700 | mg/kg | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 10 | mg/m3 | |

Diisononyl phthalate

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|------------------|------------|-------|-------|------|
| | Environment - soil | | PNEC | 30 | mg/kg | |
| | Environment - oral (animal feed) | | PNEC | 150 | mg/kg | |

Page 6 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

| | | | | | | |
|---------------------|--------------------|-----------------------------|------|-------|-------|--|
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 15,3 | mg/m3 | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 220 | mg/kg | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 4,4 | mg/kg | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 366 | mg/kg | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 51,72 | mg/m3 | |

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. BS EN 14042.
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 With long-term contact:
 Protective Viton® / fluoroelastomer gloves (EN 374)
 Minimum layer thickness in mm:
 0,7
 Permeation time (penetration time) in minutes:
 > 15
 With short-term contact:
 Protective nitrile gloves (EN 374).
 Minimum layer thickness in mm:
 0,12
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 Observe wearing time limitations for respiratory protection equipment.

Page 7 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state: | Paste, Solid |
| Colour: | According to specification |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | Not determined |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | 139 °C |
| Flash point: | n.a. |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | Not combustible. (Part III, sub-section 33.2.1 of the UN Manual of Tests and Criteria) |
| Lower explosive limit: | 0,4 Vol-% |
| Upper explosive limit: | 7,8 Vol-% |
| Vapour pressure: | 9 hPa (20°C) |
| Vapour density (air = 1): | Not determined |
| Density: | 1,37 g/cm ³ (20°C) |
| Bulk density: | Not determined |
| Solubility(ies): | Not determined |
| Water solubility: | reacts with water, Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | 420 °C (Ignition temperature) |
| Decomposition temperature: | Not determined |
| Viscosity: | Not determined |
| Explosive properties: | Product is not explosive. |
| Oxidising properties: | No |

9.2 Other information

| | |
|---------------------------|---------------------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | 7,4 % (Organic solvents) |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Page 8 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

Protect from humidity.

10.5 Incompatible materials

Water
 Alcohols
 Amines
 Acids
 Bases

10.6 Hazardous decomposition products

On contact with water - CO₂ can develop.
 CO₂ formation in closed tanks causes pressure to rise.
 Pressure increase will result in danger of bursting.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Liquimate 8100 1K-PUR grau 300 mL

Art.: 6154

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|---------|----------|-------------|---------------------------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | ATE | >2000 | mg/kg | | | calculated value |
| Acute toxicity, by inhalation: | ATE | >20 | mg/l/4h | | | calculated value, Vapours |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

Reaction mass of ethylbenzene and xylene

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|--------------------------------|----------|-----------|-------|----------|--|--|
| Acute toxicity, by oral route: | LD50 | 3523-4000 | mg/kg | Rat | Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY) | |
| Symptoms: | | | | | | drowsiness, headaches, fatigue, dizziness, unconsciousness, nausea and vomiting. |

Titanium dioxide

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|----------------------------------|----------|-------|---------|----------|--|--------------|
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LD50 | >6,8 | mg/l/4h | Rat | | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |

Page 9 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

| | | | | | | |
|---|-------|------|---------|------------------------|--|---|
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Mechanical irritation possible. |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | Not sensitising |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitising |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | (Ames-Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | | | | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | No indications of such an effect. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Not irritant (respiratory tract). |
| Symptoms: | | | | | | coughing, Irritant to mucosa of the nose and throat |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 3500 | mg/kg/d | Rat | | 90d |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 10 | mg/m3 | Rat | | 90d |

| Diisononyl phthalate | | | | | | |
|---|----------|--------|---------|-----------|--|-----------------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >10000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >3160 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LC50 | >4,4 | mg/l/4h | Rat | | Aerosol |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | | | Not sensitising |
| Germ cell mutagenicity: | | | | Mammalian | | No indications of such an effect. |
| Carcinogenicity: | | | | | | No indications of such an effect. |
| Reproductive toxicity: | | | | | | No indications of such an effect. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | No indications of such an effect. |
| Symptoms: | | | | | | diarrhoea, nausea and vomiting. |

| Calcium carbonate | | | | | | |
|-------------------|----------|-------|------|----------|-------------|-------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |

Page 10 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

| | | | | | | |
|------------------------------------|------|-------|---------|--------|--|---|
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | OECD 420 (Acute Oral toxicity - Fixe Dose Procedure) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >3 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Mechanical irritation possible. |
| Respiratory or skin sensitisation: | | | | | | No (skin contact) |
| Germ cell mutagenicity: | | | | | in vitro | Negative |
| Carcinogenicity: | | | | | | Negative, administered as Ca-lactate |
| Reproductive toxicity: | | | | | | Negative, administered as Ca-carbonate |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Liquimate 8100 1K-PUR grau 300 mL
Art.: 6154

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|----------|-------------|---|
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | | n.d.a. |
| Other information: | AOX | | 10-20 | % | | | Contains organically bound halogens, which may contribute to the AOX value in wastewater. |
| Other information: | | | | | | | DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a. |

Reaction mass of ethylbenzene and xylene

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--------------------------------------|----------|------|-------|------|----------|--|-----------------------|
| 12.2. Persistence and degradability: | | 28d | 90 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |

Page 11 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.10.2019 / 0019
Replacing version dated / version: 07.03.2017 / 0018
Valid from: 30.10.2019
PDF print date: 30.10.2019
Liquimate 8100 1K-PUR grau 300 mL
Art.: 6154

| | | | | | | | |
|--|------|-----|------|------|---------------------------------|--|-------------------------------------|
| 12.3. Bioaccumulative potential: | BCF | | 25,9 | | | | Low, Analogous conclusion |
| 12.1. Toxicity to fish: | LC50 | 96h | 2,6 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | Analogous conclusion |
| 12.1. Toxicity to daphnia: | IC50 | 24h | 1 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | Analogous conclusion |
| 12.1. Toxicity to algae: | EC50 | 72h | 2,2 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | Analogous conclusion |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Titanium dioxide | | | | | | | |
|--|-----------|------|--------|-------|---------------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | 16 | mg/l | Pseudokirchneriella subcapitata | U.S. EPA-600/9-78-018 | |
| 12.3. Bioaccumulative potential: | BCF | 14d | 19-352 | | | | Oncorhynchus mykiss |
| 12.3. Bioaccumulative potential: | BCF | 42d | 9,6 | | | | No |
| 12.4. Mobility in soil: | | | | | | | Negative |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | | | >5000 | mg/l | Escherichia coli | | |
| Toxicity to bacteria: | LC0 | 24h | >10000 | mg/l | Pseudomonas fluorescens | | |
| Toxicity to annelids: | NOEC/NOEL | | >1000 | mg/kg | Eisenia foetida | | |
| Water solubility: | | | | | | | Insoluble 20°C |

| Poly vinyl chloride | | | | | | | |
|--------------------------------------|----------|------|-------|------|----------|-------------|-------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.2. Persistence and degradability: | | | | | | | Not biodegradable |

| Diisononyl phthalate | | | | | | | |
|----------------------------|-----------|------|-------|------|-------------------------|--|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >102 | mg/l | Brachydanio rerio | 92/69/EC | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >74 | mg/l | Daphnia magna | 92/69/EC | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | >101 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 88 | mg/l | Scenedesmus subspicatus | | |
| 12.1. Toxicity to algae: | EC50 | 72h | >88 | mg/l | Scenedesmus subspicatus | 84/449/EEC C.3 | |

Page 12 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 30.10.2019 / 0019
Replacing version dated / version: 07.03.2017 / 0018
Valid from: 30.10.2019
PDF print date: 30.10.2019
Liquimate 8100 1K-PUR grau 300 mL
Art.: 6154

| | | | | | | | |
|--------------------------------------|-----------|-------|------------|-------------------------|------------------|---|-----------------------|
| 12.2. Persistence and degradability: | | 28d | 81 | % | activated sludge | Regulation (EC) 440/2008 C.4-C (DETERMINATION OF 'READY' BIODEGRADABILITY - CO ₂ EVOLUTION TEST) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 8,8-10,7 | | | | calculated value |
| 12.3. Bioaccumulative potential: | BCF | 14d | <3 | | | | Analogous conclusion |
| 12.4. Mobility in soil: | Koc | | >5000 | | | | |
| 12.4. Mobility in soil: | H (Henry) | | 0,00000149 | atm*m ³ /mol | | | |
| Toxicity to bacteria: | EC50 | 30min | >83,9 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Other organisms: | NOEC/NOEL | 56d | >982,4 | mg/kg | Eisenia foetida | | |
| Other organisms: | LC50 | 14d | >7372 | mg/kg | Eisenia foetida | OECD 207 (Earthworm, Acute Toxicity Tests) | |

| Calcium carbonate | | | | | | | |
|----------------------------|----------|------|-------|------|-------------------------|--|----------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | >14 | mg/l | Desmodesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| Toxicity to bacteria: | EC50 | 3h | >1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Toxicity to annelids: | | | | | Eisenia foetida | OECD 207 (Earthworm, Acute Toxicity Tests) | Negative |
| Water solubility: | | | 0,014 | g/l | | | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

Page 13 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

allocated under certain circumstances. (2014/955/EU)
 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances
 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
 08 04 11 adhesive and sealant sludges containing organic solvents or other hazardous substances
 08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 E.g. dispose at suitable refuse site.
 E.g. suitable incineration plant.
For contaminated packing material
 Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 7,4 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Page 14 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

Revised sections:

3, 8, 11, 12, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.

Flam. Liq. — Flammable liquid
 Acute Tox. — Acute toxicity - dermal
 Skin Irrit. — Skin irritation
 Acute Tox. — Acute toxicity - inhalation
 Asp. Tox. — Aspiration hazard
 Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 STOT RE — Specific target organ toxicity - repeated exposure

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general

Page 15 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 30.10.2019 / 0019
 Replacing version dated / version: 07.03.2017 / 0018
 Valid from: 30.10.2019
 PDF print date: 30.10.2019
 Liquimate 8100 1K-PUR grau 300 mL
 Art.: 6154

GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
 No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.