



## Safety Data Sheet

VELIND Aerosol GmbH

according to Regulation (EC) No 1907/2006

### VELIND Cockpitpflegespray neutral 300ml

Revision date: 26.02.2019

Product code: 31545

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

VELIND Cockpitpflegespray neutral 300ml

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Use of the substance/mixture**

Automotive Care (spray, liquid), SURFACE CLEANERS (liquid, powder, gel neat, spray neat) for consumer use

#### **Uses advised against**

No information available. Use(Usage) exclusively according to labelled intended purpose!

### 1.3. Details of the supplier of the safety data sheet

Company name:	VELIND Aerosol GmbH
Street:	Passower Chaussee 111
Place:	D-16303 Schwedt/O
Telephone:	+49 33 32 / 4 50 88 - 0
e-mail:	info@velind.de
Contact person:	Witt
e-mail:	qs@velind.de
Internet:	www.velind.de
Responsible Department:	QS

Telefax: +49 33 32 / 4 50 88 - 30

Telephone: 18

### 1.4. Emergency telephone number:

GGIZ der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: +49 3 61 / 7 30 73 -0

#### **Further Information**

Emergency - Phonecalls to +49 (0) 33 32 / 4 50 88 16  
(during office-hours from 8.00 a.m. to 4.00 p.m.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### **Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### **Regulation (EC) No. 1272/2008**

#### **Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Signal word: Danger

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 2 of 13

**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of the Contents/container of waste according to with local/national regulations applicable legislation.

**Special labelling of certain mixtures**

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Labelling of packages where the contents do not exceed 125 ml****Signal word:**

Danger

**Pictograms:****Hazard statements**

H222-H229-H336

**Precautionary statements**

P101-P102-P103-P210-P211-P251-P261-P271-P304+P340-P312-P403+P233-P405-P410+P412-P501

**2.3. Other hazards**

In use, may form flammable/explosive vapour-air mixture. Inhalation causes narcotic effects/intoxication.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Aerosol



## Safety Data Sheet

VELIND Aerosol GmbH

according to Regulation (EC) No 1907/2006

### VELIND Cockpitpflegespray neutral 300ml

Revision date: 26.02.2019

Product code: 31545

Page 3 of 13

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			45 - < 50 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411 EUH066			
64-17-5	ethanol, ethyl alcohol			5 - < 10 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319 EUH066			

Full text of H and EUH statements: see section 16.

#### Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated, saturated clothing immediately. First aider: Pay attention to self-protection! Move victim out of danger zone.

#### After inhalation

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Provide fresh air. Move victim out of danger zone. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Not applicable, because aerosol. If it does, consult a doctor immediately and show him box or label.

### 4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur::

Intoxication. unconsciousness. Headache. drowsiness. Dizziness. Depression of the central nervous system.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. This information is not available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder. alcohol resistant foam. Water spray. dry extinguishing powder. Water fog.

#### Unsuitable extinguishing media

Water. High power water jet.

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 4 of 13

**5.2. Special hazards arising from the substance or mixture**

Extremely flammable aerosol. Vapours can form explosive mixtures with air. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours are heavier than air and will spread at floor level. Beware of reignition. Contains gas under pressure; may explode if heated. (H280) Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide Carbon dioxide.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Special protective equipment for firefighters In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Remove according to the regulations.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Keep away from sources of ignition - No smoking.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Provide fresh air. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area. Collect in closed containers for disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use only outdoors or in a well-ventilated area. Keep away from sources of ignition - No smoking. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Keep out of the reach of children. Keep away from hot surfaces. Read label before use. Observe in addition any national regulations!

**Advice on protection against fire and explosion**

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 5 of 13

temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Maximum storage temperature: 50°C Further information concerning storage conditions: The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

**Hints on joint storage**

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Keep away from: Oxidizing agents. strong alkalis.

**Further information on storage conditions**

Fire class: C

**7.3. Specific end use(s)**

Automotive Care (spray, liquid), SURFACE CLEANERS (liquid, powder, gel neat, spray neat) for consumer use

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	609 mg/m³
	Worker DNEL, long-term	inhalation	systemic	2035 mg/m³
64-17-5	ethanol, ethyl alcohol			
	Worker DNEL, acute	inhalation	local	1900 mg/m³
	Worker DNEL, long-term	inhalation	systemic	950 mg/m³
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, acute	inhalation	local	950 mg/m³
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m³
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day

according to Regulation (EC) No 1907/2006

### VELIND Cockpitpflegespray neutral 300ml

Revision date: 26.02.2019

Product code: 31545

Page 6 of 13

#### PNEC values

CAS No	Substance	
Environmental compartment		Value
64-17-5	ethanol, ethyl alcohol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/l
Marine sediment		2,9 mg/l
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg

#### 8.2. Exposure controls



#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations. Exposure controls / Personal protection equipment

#### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not eat, drink, smoke, sniff. Personal protection equipment. Contaminated work clothing should not be allowed out of the workplace. Technical ventilation of workplace.

#### Eye/face protection

Wear eye protection/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber). Butyl rubber.

Thickness of glove material: 0,7mm

Breakthrough times and swelling properties of the material must be taken into consideration.

Protect skin by using skin protective cream. Set out skin protection guidelines.

Apply skin care products after work.

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing . .

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values. Filtering device (full mask or mouthpiece) with filter:

#### Environmental exposure controls

No information available.

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 7 of 13

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol, Active component: flüssig
Colour:	colourless
Odour:	characteristic
pH-Value:	not applicable

**Changes in the physical state**

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not determined

**Flammability**

Solid:	not applicable
Gas:	not applicable

**Explosive properties**

not explosive. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	1 vol. %
Upper explosion limits:	9,4 vol. %
Ignition temperature:	not determined

**Auto-ignition temperature**

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure:	not determined
Density:	0,735 (Active component) g/cm <sup>3</sup>
Bulk density:	not applicable
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

**Solubility in other solvents**

not determined

Partition coefficient:	not determined
Viscosity / dynamic:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

**9.2. Other information**

Solid content:	not determined
----------------	----------------

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol. The product has not been tested.

**10.2. Chemical stability**

Stable with proper storage and handling.

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 8 of 13

**10.3. Possibility of hazardous reactions**

No decomposition if used as intended

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Refer to chapter 7.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on naked flames or any incandescent material.

Heating causes rise in pressure with risk of bursting. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

**10.5. Incompatible materials**

Refer to chapter 7.

Materials to avoid: Oxidizing agents.

**10.6. Hazardous decomposition products**

Refer to chapter 5.

No decomposition if used as intended

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

Mixture not tested. There are no data available on the preparation/mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 mg/kg	>2000 Rat		
	dermal	LD50 mg/kg	>2000 Rat		
	inhalation (4 h) vapour	LC50	>20 mg/l Rat		
64-17-5	ethanol, ethyl alcohol				
	oral	LD50 mg/kg	>2000 Rat		
	dermal	LD50 mg/kg	>2000 Rabbit		
	inhalation (4 h) vapour	LC50	>20 mg/l Rat		

**Irritation and corrosivity**

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

No data available

**Sensitising effects**

Based on available data, the classification criteria are not met.

No data available

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

No data available

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 9 of 13

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

No data available

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. There are no data available on the mixture itself. No data available

**Practical experience****Observations relevant to classification**

The evaluation based on subjective human observations: May cause drowsiness or dizziness. Headache.

**Further information**

Mixture not tested. There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information****12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Mixture not tested. There are no data available on the preparation/mixture itself.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
	Acute fish toxicity	LC50 >1 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50 >1 mg/l	72 h	Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50 >1 mg/l	48 h	Daphnia magna			
64-17-5	ethanol, ethyl alcohol						
	Acute fish toxicity	LC50 >100 mg/l	96 h	Leuciscus idus (golden orfe)			
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Chlorella vulgaris			
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna			

**12.2. Persistence and degradability**

The product has not been tested. No data available

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,32

**BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol, ethyl alcohol	0,66		

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 10 of 13

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

No data available

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Mixture not tested.

There are no data available on the preparation/mixture itself.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. The waste codes are recommendations based on the scheduled use of this products. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

**Waste disposal number of used product**

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors; hazardous waste

**Waste disposal number of contaminated packaging**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Recommendation: Dispose of waste according to applicable legislation. E.g. Dispose of contents/container to industrial incineration plant. Or: Dispose of this material and its container to hazardous or special waste collection point.

Do not empty into drains.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number:** UN1950**14.2. UN proper shipping name:** AEROSOLS**14.3. Transport hazard class(es):** 2

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Transport category: 2

Tunnel restriction code: D

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 11 of 13

**Other applicable information (land transport)**

E0

**Inland waterways transport (ADN)**

<b>14.1. UN number:</b>	UN1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
Hazard label:	2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

**Other applicable information (inland waterways transport)**

E0

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2, see SP63

Special Provisions:

63, 190, 277, 327, 344, 959

Limited quantity:

See SP277

EmS:

F-D, S-U

**Other applicable information (marine transport)**

E0

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Warning: Flammable gases. Persons employed in transporting dangerous goods must be trained. Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available

**Other applicable information**

Minimum amount regulations: &lt; 1 litre

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane

Entry 28: butane; isobutane

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS  
(SEVESO III):

according to Regulation (EC) No 1907/2006

**VELIND Cockpitpflegespray neutral 300ml**

Revision date: 26.02.2019

Product code: 31545

Page 12 of 13

Additional information: E2

**Additional information**

Regulation (EC) No. 648/2004 (Detergents regulation). Labelling for contents according to regulation (EC) No 648/2004, annex 7: Yes.

Aerosol directive (75/324/EEC).

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,15.

These details refer to the products as it is delivered.

Notice the directions for use on the label.

\* Data changed compared with the previous version

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road )

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

**Relevant H and EUH statements (number and full text)**

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for



## Safety Data Sheet

VELIND Aerosol GmbH

according to Regulation (EC) No 1907/2006

### VELIND Cockpitpflegespray neutral 300ml

Revision date: 26.02.2019

Product code: 31545

Page 13 of 13

adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*