



Prestone

REDEX

SIMONIZ

## SAFETY DATA SHEET

### GLOSS BLACK PAINT

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** GLOSS BLACK PAINT

**Product number** RF0171C

**REACH registration notes** This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** A Holts Car Care Product  
 Holt Lloyd International Ltd  
 Barton Dock Road  
 Stretford  
 Manchester  
 M32 0YQ - England, UK  
 +44 (0) 161 866 4800  
 FAX +44 (0) 161 866 4854  
[www.holtsauto.com](http://www.holtsauto.com)

**Contact person** Contact Email address: [info@holtsauto.com](mailto:info@holtsauto.com)

##### 1.4. Emergency telephone number

**Emergency telephone** UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229

**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336

**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** Xi;R36. F+;R12. R66,R67.

##### 2.2. Label elements

**Pictogram**



**Signal word**

Danger

## GLOSS BLACK PAINT

<b>Hazard statements</b>	H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated
<b>Precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/ doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/ attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P501 Dispose of contents/ container in accordance with local regulations.
<b>Contains</b>	ACETONE, BUTYL ACETATE -norm, BUTANOL-norm, BUTANONE

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>DIMETHYL ETHER</b>	30-60%
CAS number: 115-10-6	EC number: 204-065-8
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12
Press. Gas	
<b>ACETONE</b>	10-30%
CAS number: 67-64-1	EC number: 200-662-2
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
<b>BUTANE</b>	5-10%
CAS number: 106-97-8	EC number: 203-448-7
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12
Press. Gas	

## GLOSS BLACK PAINT

<b>BUTYL ACETATE -norm</b>	<b>5-10%</b>
CAS number: 123-86-4	EC number: 204-658-1
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 R66 R67
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>	<b>5-10%</b>
CAS number: 108-65-6	EC number: 203-603-9
<b>Classification</b> Flam. Liq. 3 - H226	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 Xi;R36
<b>ISOBUTANE</b>	<b>5-10%</b>
CAS number: 75-28-5	EC number: 200-857-2
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12
<b>BUTANONE</b>	<b>1-5%</b>
CAS number: 78-93-3	EC number: 201-159-0
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xi;R36 R66 R67
<b>BUTANOL-norm</b>	<b>1-5%</b>
CAS number: 71-36-3	EC number: 200-751-6
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 Xn;R22 Xi;R37/38,R41 R67
<b>ALUMINIUM POWDER (PYROPHORIC)</b>	<b>1-5%</b>
CAS number: 7429-90-5	EC number: 231-072-3
<b>Classification</b> Pyr. Sol. 1 - H250 Water-react. 2 - H261	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R15,R17

## GLOSS BLACK PAINT

<b>XYLENE</b>	1-5%
CAS number: 1330-20-7	EC number: 215-535-7
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting.
<b>Skin contact</b>	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Use fire-extinguishing media suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Move containers from fire area if it can be done without risk.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

#### 6.4. Reference to other sections

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

## GLOSS BLACK PAINT

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### **7.2. Conditions for safe storage, including any incompatibilities**

**Storage class** Flammable compressed gas storage.

### **7.3. Specific end use(s)**

#### **SECTION 8: Exposure Controls/personal protection**

##### **8.1. Control parameters**

##### **Occupational exposure limits**

##### **DIMETHYL ETHER**

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m<sup>3</sup>

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **BUTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

##### **BUTYL ACETATE -norm**

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

##### **2-METHOXY-1-METHYLETHYL ACETATE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m<sup>3</sup>(Sk)

##### **ISOBUTANE**

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

##### **BUTANONE**

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m<sup>3</sup>(Sk)

##### **BUTANOL-norm**

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m<sup>3</sup>(Sk)

##### **ALUMINIUM POWDER (PYROPHORIC)**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup>

##### **XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### **8.2. Exposure controls**

## GLOSS BLACK PAINT

### Protective equipment



#### Eye/face protection

The following protection should be worn: Chemical splash goggles.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. EN374 It is recommended that gloves are made of the following material: Rubber (natural, latex).

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.

#### Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

**Appearance** Aerosol.

**Colour** Black.

**Flash point** Not applicable.

**Upper/lower flammability or explosive limits** Lower flammable/explosive limit: 1.6% Upper flammable/explosive limit: 18.6%

**Relative density** ~0.748 @ °C

**Auto-ignition temperature** 235°C

### 9.2. Other information

**Volatility** 91.9%

**Volatile organic compound** This product contains a maximum VOC content of 687.5 g/litre.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Thermal decomposition or combustion products may include the following substances:

Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

## GLOSS BLACK PAINT

### Acute toxicity - oral

ATE oral (mg/kg) 20,000.0

### Acute toxicity - dermal

ATE dermal (mg/kg) 110,000.0

### Acute toxicity - inhalation

ATE inhalation (gases ppm) 450,000.0

ATE inhalation (vapours mg/l) 1,100.0

ATE inhalation (dusts/mists mg/l) 150.0

### **Inhalation**

Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache.

### **Ingestion**

No harmful effects expected from quantities likely to be ingested by accident.

### **Skin contact**

Prolonged and frequent contact may cause redness and irritation.

### **Eye contact**

Irritating to eyes. Repeated exposure may cause chronic eye irritation.

### **Route of entry**

Inhalation Skin and/or eye contact

## SECTION 12: Ecological Information

### **Ecotoxicity**

Not regarded as dangerous for the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Disposal methods**

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion.

## SECTION 14: Transport information

### 14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

### 14.2. UN proper shipping name

## GLOSS BLACK PAINT

**Proper shipping name** AEROSOLS  
**(ADR/RID)**

**Proper shipping name (IMDG)** AEROSOLS

**Proper shipping name (ICAO)** AEROSOLS

**Proper shipping name (ADN)** AEROSOLS

**14.3. Transport hazard class(es)**

**ADR/RID class** 2.1

**ADR/RID classification code** 5F

**ADR/RID label** 2.1

**IMDG class** 2.1

**ICAO class/division** 2.1

**ADN class** 2.1

**Transport labels**



**14.4. Packing group**

**ADR/RID packing group** None

**IMDG packing group** None

**ADN packing group** None

**ICAO packing group** None

**14.5. Environmental hazards**

**Environmentally hazardous substance/marine pollutant**

No.

**14.6. Special precautions for user**

**EmS** F-D, S-U

**ADR transport category** 2

**Tunnel restriction code** (D)

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78**

**and the IBC Code**

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulations** EH40/2005 Workplace exposure limits.

## GLOSS BLACK PAINT

<b>EU legislation</b>	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Authorisations (Title VII Regulation 1907/2006)</b>	No specific authorisations are known for this product.
<b>Restrictions (Title VIII Regulation 1907/2006)</b>	No specific restrictions on use are known for this product.

### **15.2. Chemical safety assessment**

#### **SECTION 16: Other information**

<b>Revision date</b>	24/08/2015
<b>Revision</b>	1
<b>Supersedes date</b>	13/08/2013
<b>SDS number</b>	14293
<b>Risk phrases in full</b>	<p>R10 Flammable.  R11 Highly flammable.  R12 Extremely flammable.  R15 Contact with water liberates extremely flammable gases.  R17 Spontaneously flammable in air.  R20/21 Harmful by inhalation and in contact with skin.  R22 Harmful if swallowed.  R36 Irritating to eyes.  R37/38 Irritating to respiratory system and skin.  R38 Irritating to skin.  R41 Risk of serious damage to eyes.  R66 Repeated exposure may cause skin dryness or cracking.  R67 Vapours may cause drowsiness and dizziness.</p>
<b>Hazard statements in full</b>	<p>H220 Extremely flammable gas.  H222 Extremely flammable aerosol.  H225 Highly flammable liquid and vapour.  H226 Flammable liquid and vapour.  H229 Pressurised container: may burst if heated  H250 Catches fire spontaneously if exposed to air.  H261 In contact with water releases flammable gases.  H302 Harmful if swallowed.  H312 Harmful in contact with skin.  H315 Causes skin irritation.  H318 Causes serious eye damage.  H319 Causes serious eye irritation.  H332 Harmful if inhaled.  H335 May cause respiratory irritation.  H336 May cause drowsiness or dizziness.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.