

Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

· Article number: MN4112 · UFI: P1DC-P0S5-K00E-HJMG

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Heat transfer fluid

· 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: UAB "SCT Lubricants" Silutes Pl. 119 LIT-95112 KLAIPEDA LITHUANIA renata@sct.lt

· Further information obtainable from: Product safety department.

· 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

STOT RE 2 H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.



Acute Tox. 4 H302 Harmful if swallowed.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS08

- · Signal word Warning
- Hazard-determining components of labelling:

ethane-1,2-diol ethanediol

3,5,5-trimethylhexanoate

Hazard statements

H302 Harmful if swallowed.

(Contd. on page 2)



Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

(Contd. of page 1)

H319 Causes serious eye irritation.

H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear eye protection / face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P330 Rinse mouth.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous compoi	nents:	
CAS: 107-21-1	ethanediol	92–96%
EINECS: 203-473-3	STOT RE 2, H373; Acute Tox. 4, H302	
	3,5,5-trimethylhexanoate	2.1–2.8%
EINECS: 299-890-3	Skin Corr. 1, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	
· Not dangerous sub	stances	
CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	2–5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

Foam

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

E -



Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

107-21-1 ethanediol (95.0%)

OEL Short-term value: 40 mg/m³, 104 ppm Long-term value: 52 mg/m³, 20 ppm Sk, IOELV

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- Physical state Fluid

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

(Contd. of page 4)

· Colour: Red

· Odour: Product specific · Odour threshold: Not determined.

<-18 °C Melting point/freezing point:

· Boiling point or initial boiling point and

boiling range 197 °C (107-21-1 ethanediol)

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 3.2 Vol % · Upper: 53 Vol %

· Flash point: 111 °C (107-21-1 ethanediol) · Auto-ignition temperature: 410 °C (107-21-1 ethanediol)

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

· Solubility

· water at 20 °C: 1.000 q/l

Partition coefficient n-octanol/water (log

Not determined.

· Vapour pressure at 20 °C: 0.1 hPa (107-21-1 ethanediol)

Density and/or relative density

Density at 20 °C: 1.114 g/cm³ · Relative density Not determined. Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquid

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Water: 2-5 % · Solids content: >0.9-2 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit

flammable gases in contact with water Void **Oxidising liquids** Void

(Contd. on page 6)



Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

(Contd. of page 5)

Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

Void
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC	50 values relevant for classification:
ATE (A	cute Toxicity Estimates)
Oral	LD50 17,857–23,810 mg/kg
407.04	A all and the

	107-21-1 ethanediol		
Oral	LD50	5,840 mg/kg (rat)	
Dermal	LD50	9,530 mg/kg (rabbit)	

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 7)



Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

(Contd. of page 6)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Euro	pean waste catalogue
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6	Acute Toxicity

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number	mat was wellated
ADR, ADN, IMDG, IATA	not regulated
14.2 UN proper shipping name	
ADR, ADN, IMDG, IATA	not regulated
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	not regulated
14.4 Packing group	
ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi	ing to
IMO instruments	Not applicable.
UN "Model Regulation":	not regulated

— IE

Page 8/8



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.05.2024 Version number 2 (replaces version 1) Revision: 24.05.2024

Trade name: MANNOL 4112 Antifreeze AF12+ Longlife

(Contd. of page 7)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H373 May cause damage to organs through prolonged or repeated exposure.
- · Department issuing SDS: Product safety department.
- · Contact: Mrs. Zubaite
- Date of previous version: 15.05.2024
 Version number of previous version: 1
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1: Skin corrosion/irritation – Category 1

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.