Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Eurolub Cockpit-Spray Orange - 400 ml

· Article number: 00050 7

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the preparation: Surface protection
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

EUROLUB GmbH

Freisinger Strasse 25-27 85386 Eching bei München

Telefon: 08165 / 95 91 - 0 Fax: 08165 / 95 91 - 20 Email: info@eurolub.de

· Further information obtainable from:

Herr Günter Dietz

Telefon: +49-(0)8165 / 95 91-0 (über Zentrale vermittelt)

Email: info@eurolub.de

· Emergency telephone number:

Beratungsstelle bei Vergiftungen, Mainz

Tel. 0049 (0) 6131 / 19240

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R38: Irritating to skin.

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 1)



F+; Extremely flammable

R12: Extremely flammable.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07, GHS09
- · Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P321 Specific treatment (see on this label).

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- $\cdot \textit{Description:} \ \textit{Mixture of substances listed below with nonhazardous additions.}$

(Contd. on page 3)

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 2)

	(00	iliu. Of page 2
· Dangerous components:		
CAS: 106-97-8	butane	25-50%
EINECS: 203-448-7	F+ R12	
Index number: 601-004-00-0	Flam. Gas 1, H220; Press. Gas, H280	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	25-50%
EINECS: 265-151-9	X Xn R65; X Xi R38; № F R11; № N R51/53	
Index number: 649-328-00-1	R67	
	 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 	
CAS: 74-98-6	propane	10-<25%
EINECS: 200-827-9	F+R12	
Index number: 601-003-00-5	Flam. Gas 1, H220; Press. Gas, H280	
· Regulation (EC) No 648/200	4 on detergents / Labelling for contents	
aliphatic hydrocarbons		≥ 30%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Recommended storage temperature: 10-30 °C.

· Specific end use(s) No further relevant information available.

* 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- Respiratory protection: When used properly and under normal conditions, breathing protection is not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 4)

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · As protection from splashes gloves made of the following materials are suitable: PVC or PE gloves
- · Eye protection:

VOC (EC)



Tightly sealed goggles

· Body protection: Light weight protective clothing

9 Physical and chemical properties		
· Information on basic physical of General Information · Appearance:	and chemical properties	
Form:	Aerosol	
Colour:	Colourless	
· Odour:	Fruit-like	
· Odour threshold:	Not determined.	
· pH-value:	Not applicable for an aerosol *	
· Change in condition		
Melting point/Melting range:		
Boiling point/Boiling range:	Not applicable, as aerosol.	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	365 °C	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Protect from sunlight and temperatures above 50 °C. Development of explosive vapor/air mixtures.	
· Explosion limits:		
Lower:	1,0 Vol %	
Upper:	10,9 Vol %	
· Vapour pressure at 20 °C:	4200 hPa	
· Density at 20 °C:	0,651 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		

87,95 %

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 5)

	(**************************************
VOCV (CH)	87,95 %
· Other information	* The final mixture in the aerosol is formed only after the addition of the pressurized gas. Some data are not measurable in a hermetically sealed, pressurized container.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

*11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 v	· LD/LC50 values relevant for classification:		
106-97-8 b	106-97-8 butane		
Inhalative	Inhalative LC50/4 h 658 mg/l (rat)		
64742-49-0	0 Naphtha	(petroleum), hydrotreated light	
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>5 mg/l (rat)	
74-98-6 pr	opane		
Inhalative	LC50/4 h	>20 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

*12 Ecological information

- · Toxicity
- · Aquatic toxicity:

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50 1-10 mg/l (Algen)

1-10 mg/l (aquatische Invertebraten)

LC50 1-10 mg/l (fish)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 6)

- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

The waste codes are recommendations based on the possible use of this product. Because of the special use and disposal conditions at the user might,

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Tra	nsport	infoi	rmai	ion
--------	--------	-------	------	-----

· UN-Number	
· ADR, IMDG, IATA	UN1950

· UN proper shipping name

· ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases.

· Label 2.

· IMDG, IATA



· Class 2.1 · Label 2.1

(Contd. on page 8)

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 7)

D //	(Contd. of page /
· Packing group	** * 1
· ADR, IMDG, IATA	Void
· Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light
· Marine pollutant:	No
· Special precautions for user	Warning: Gases.
· Danger code (Kemler):	•
· EMS Number:	F- D , S - U
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot ADR$	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D
· UN ''Model Regulation'':	UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

st 15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R67 Vapours may cause drowsiness and dizziness.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

(Contd. on page 9)

Printing date 17.01.2014 Version number 7 Revision: 17.01.2014

Trade name: Eurolub Cockpit-Spray Orange - 400 ml

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent • * Data compared to the previous version altered.