

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 14

SDS No.: 228588

V008.3 Revision: 20.01.2025

printing date: 03.07.2025

Replaces version from: 03.07.2024

LOCTITE SF 7100 known as Loctite 7100

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7100 known as Loctite 7100 UFI: 8JC1-JW20-Q209-DUPS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Leak Detector

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Aerosols Category 3

H229 Pressurized container: May burst if heated.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word: Warning

Page 2 of 14

V008.3

SDS No.: 228588

Hazard statement: H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statement: P251 Do not pierce or burn, even after use.

> P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P102 Keep out of reach of children.

Precautionary statement:

Response

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Poly(oxy-1,2-ethanediyl), α- (carboxymethyl)-ω-hydroxy-, C12-14-alkyl ethers 220622-96-8	2,5-< 3 %	Eye Dam. 1, H318		
ammonia, aqueous solution 1336-21-6 215-647-6 01-2119488876-14	0,25-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 2, H411 Skin Corr. 1B, H314 Acute Tox. 4, Inhalation, H332 STOT SE 3, H335	STOT SE 3; H335; C >= 5 % ===== M acute = 1 ===== inhalation:	EU OEL

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

V008.3

Eve contact

SDS No.: 228588

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Page 4 of 14

V008.3

SDS No.: 228588

Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Store in a cool, well-ventilated place. Keep away from heat and direct sunlight. Refer to Technical Data Sheet.

7.3. Specific end use(s)

Leak Detector

V008.3

SDS No.: 228588

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES]		10	Time Weighted Average (TWA):		EH40 WEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL VAPOUR AND PARTICULATES]	150	474	Time Weighted Average (TWA):		EH40 WEL
Ammonia, aqueous solution 1336-21-6 [Ammonia, anhydrous]	35	25	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Ammonia, aqueous solution 1336-21-6 [Ammonia, anhydrous]	25	18	Time Weighted Average (TWA):		EH40 WEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	50	36	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	20	14	Time Weighted Average (TWA):	Indicative	ECTLV

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL]		10	Time Weighted Average (TWA):		IR_OEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL]	150	470	Time Weighted Average (TWA):		IR_OEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	50	36	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	20	14	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	50	36	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ammonia, aqueous solution 1336-21-6 [AMMONIA, ANHYDROUS]	20	14	Time Weighted Average (TWA):	Indicative	ECTLV

Page 6 of 14

V008.3

SDS No.: 228588

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental		Value				Remarks
	Compartment	perioa	ma/l		ma/lra	others	
			mg/l	ppm	mg/kg	others	
ammonia, aqueous solution 1336-21-6	aqua (freshwater)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (marine water)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (intermittent releases)		0,0068 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
ammonia, aqueous solution 1336-21-6	Workers	inhalation	Long term exposure - systemic effects		47,6 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	inhalation	Acute/short term exposure - systemic effects		47,6 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	inhalation	Long term exposure - local effects		14 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - local effects		36 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	dermal	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	dermal	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Long term exposure - systemic effects		23,8 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Acute/short term exposure - systemic effects		23,8 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Long term exposure - local effects		2,8 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	inhalation	Acute/short term exposure - local effects		7,2 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	dermal	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	dermal	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	oral	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	oral	Acute/short term exposure - systemic effects		6,8 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Page 7 of 14

V008.3

SDS No.: 228588

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly

ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eve protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form liquid

Colourless / Colorless Colour Odor characteristic Physical state liauid

Melting point Not applicable, Product is a liquid

Initial boiling point 100 °C (212 °F)no method / method unknown

Flammability The product is not flammable.

Explosive limits

2.6%(V);lower 12,6 %(V); upper

Upper/lower explosion limit

104 °C (219.2 °F) Flash point

Auto-ignition temperature Not applicable, The product is not flammable.

Not applicable, Substance/mixture is not self-reactive, no organic Decomposition temperature peroxide and does not decompose under foreseen conditions of use

7,5

(20 °C (68 °F); Conc.: 100 %)

Viscosity (kinematic) Currently under determination

Solubility (qualitative) Miscible

(20 °C (68 °F); Solvent: Water)

Not applicable Partition coefficient: n-octanol/water

Mixture 23,0000000 hPa Vapour pressure

(20 °C (68 °F))

Density 1,017 g/cm3 None

(20 °C (68 °F))

Relative vapour density: Currently under determination

Particle characteristics Not applicable Product is a liquid

SDS No.: 228588 V008.3

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Aerosols:

Classified as Aerosol category 3 because it does not meet the criteria for inclusion in Category 1 or Category 2.

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

No data available.

Acute dermal toxicity:

No data available.

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
ammonia, aqueous	Acute	6570 ppm	gas	4 h		Expert judgement
solution	toxicity					
1336-21-6	estimate					
	(ATE)					

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous solution	corrosive	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1336-21-6				,

V008.3

SDS No.: 228588

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous	corrosive			not specified
solution				
1336-21-6				

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
ammonia, aqueous	not sensitising	not specified	guinea pig	not specified
solution				
1336-21-6				

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
ammonia, aqueous	negative	bacterial reverse	not specified		OECD Guideline 471
solution		mutation assay (e.g			(Bacterial Reverse Mutation
1336-21-6		Ames test)			Assay)
ammonia, aqueous	negative	intraperitoneal		mouse	OECD Guideline 474
solution					(Mammalian Erythrocyte
1336-21-6					Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
ammonia, aqueous solution 1336-21-6	not carcinogenic	oral: feed	104 w daily	rat		OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
ammonia, aqueous	NOAEL P 408 mg/kg	screening	oral:	rat	OECD Guideline 422
solution			unspecified		(Combined Repeated Dose
1336-21-6					Toxicity Study with the
					Reproduction /
					Developmental Toxicity
					Screening Test)

STOT-single exposure:

No data available.

SDS No.: 228588 V008.3

No data available.

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
ammonia, aqueous solution	LC50	0,16 - 1,1 mg/l	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
1550-21-0				Oncomynenus mykiss)	Acute Toxicity Test)
ammonia, aqueous solution	NOEC	< 0,048 mg/l	31 d	Channel catfish	OECD Guideline 215 (Fish,
1336-21-6					Juvenile Growth Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
ammonia, aqueous solution	EC50	25,4 mg/l	48 h	Daphnia magna	OECD Guideline 202
1336-21-6					(Daphnia sp. Acute
					Immobilisation Test)

${\bf Chronic\ toxicity\ (aquatic\ invertebrates):}$

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution	NOEC	0,79 mg/l	96 h	Daphnia magna	EPA OPPTS 850.1300
1336-21-6					(Daphnid Chronic Toxicity
					Test)

Toxicity (Algae):

V008.3

SDS No.: 228588

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
ammonia, aqueous solution 1336-21-6	EC50	> 1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)
ammonia, aqueous solution 1336-21-6	NOEC	1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)

Toxicity (microorganisms):

No data available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
ammonia, aqueous solution	-1,14		EU Method A.8 (Partition Coefficient)
1336-21-6			

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
ammonia, aqueous solution	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall
1336-21-6	not be conducted for inorganic substances.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Page 12 of 14

SDS No.: 228588

V008.3

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS

IATA Aerosols, non-flammable

14.3. Transport hazard class(es)

ADR	2.2
RID	2.2
ADN	2.2
IMDG	2.2
IATA	2.2

14.4. Packing group

ADR RID ADN **IMDG IATA**

14.5. **Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR not applicable

Page 13 of 14

V008.3

SDS No.: 228588

Tunnelcode: (E)
RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

VOC content 10 - 15 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

V008.3

SDS No.: 228588

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

Substance with a Union workplace exposure limit

EU EXPLD 1:

Substance listed in Annex I, Reg (EC) No. 2019/1148

EU EXPLD 2

Substance listed in Annex II, Reg (EC) No. 2019/1148

SVHC:

Substance of very high concern (REACH Candidate List)

PBT:

Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.