

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** SONAX Protect+Shine**Article number:**

06305000, 06306000, 06307050

**UFI:** JJG0-S0Q7-100T-J61X**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Car care product

Professional uses

**Uses advised against** Consumer uses: Private households / general public / consumers**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

**Further information obtainable from:**

Product safety

E-mail: [erp@sonax.de](mailto:erp@sonax.de)

Phone: + +49 (0) 8431 53 217

**United Kingdom:**

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: [info@aaoil.co.uk](mailto:info@aaoil.co.uk)**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2            H315 Causes skin irritation.

Eye Dam. 1            H318 Causes serious eye damage.

Aquatic Chronic 3    H412 Harmful to aquatic life with long lasting effects.

**Additional information:**

Sustained combustibility test ISO 9038/UN manual of tests and criteria (32.5.2):

no self-sustained combustion

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS05

**Signal word** Danger**Hazard-determining components of labelling:**

Dipalmoylisopropyl Dimonium Methosulfate

**Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 1)

**Precautionary statements**

P280 Wear protective gloves/eye protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH208 Contains benzyl salicylate. May produce an allergic reaction.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

**vPvB:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

**Determination of endocrine-disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

**Description:** Tensides, care additives, alcohol in aqueous solution.

**Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-<15%
CAS: 1474044-71-7 EC No 939-685-4 Reg.nr.: 01-2119983493-26-xxxx	1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters with fatty acids, C18 unsatd., Me sulfates (salts) Alternative CAS number: 95009-13-5 ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Aquatic Chronic 3, H412	5-<10%
CAS: 9004-78-8 NLP: 500-013-6	Phenol polyethoxilate ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319	5-<10%
CAS: 5131-66-8 EINECS: 225-878-4 Reg.nr.: 01-2119475527-28-xxxx	3-butoxypropan-2-ol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	3-<5%
CAS: 71750-79-3 EC number: 615-336-9	Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me ⚠ Skin Corr. 1B, H314	1-<3%
CAS: 69011-36-5 EC No 931-138-8	isotridecanol, ethoxylated (>5-20EO) ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: 1 % ≤ C < 10 %	1-<3%
CAS: 61791-26-2 NLP: 500-153-8	Tallow alkylamine ethoxylate ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315	<1%
CAS: 118-58-1 EINECS: 204-262-9 Reg.nr.: 01-2119969442-31-xxxx	benzyl salicylate ⚠ Eye Irrit. 2, H319; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	<0.25%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 2)

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Remove soiled clothing**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:**

Wash the areas of skin affected with water and a mild detergent.

If skin irritation continues, consult a doctor.

**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Eye irritation / Eye damage

Skin irritation

Allergic reactions

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters****Protective equipment:**

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation**For non-emergency personnel**

Avoid contact with the eyes and skin.

Wear protective clothing.

**For emergency responders** Wear protective equipment. Keep unprotected persons away.**6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** No special precautions are necessary if used correctly.**Information about fire - and explosion protection:** No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.**Information about storage in one common storage facility:**

Store away from foodstuffs.

Observe local/state/federal regulations.

(Contd. on page 4)

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 3)

### Further information about storage conditions:

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

##### CAS: 67-63-0 propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

OEL (Ireland) Short-term value: 400 ppm  
Long-term value: 200 ppm  
Sk

#### Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

#### DNELs

##### CAS: 67-63-0 propan-2-ol

Oral	DNEL	26 mg/kg (consumer) (chronic effects (1d))
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d)) 888 mg/kg (worker) (chronic effects (1d))
Inhalative	DNEL	89 mg/m <sup>3</sup> (consumer) (chronic effects) 500 mg/m <sup>3</sup> (worker) (chronic effects)

##### CAS: 1474044-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters with fatty acids, C18 unsatd., Me sulfates (salts)

Oral	DNEL	1.25 mg/kg bw/day (consumer) (longterm systematic effects)
Dermal	DNEL	56.25 mg/kg bw/day (consumer) (longterm systematic effects) 112.5 mg/kg bw/day (worker) (longterm systematic effects)
Inhalative	DNEL	2.17 mg/m <sup>3</sup> (consumer) (longterm systematic effects) 8.72 mg/m <sup>3</sup> (worker) (longterm systematic effects)

##### CAS: 5131-66-8 3-butoxypropan-2-ol

Oral	DNEL	12.5 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	22 mg/kg (consumer) (longterm systematic effects) 52 mg/kg (worker) (longterm systematic effects)
Inhalative	DNEL	43 mg/m <sup>3</sup> (consumer) (longterm systematic effects) 147 mg/m <sup>3</sup> (worker) (longterm systematic effects)

#### PNECs

##### CAS: 67-63-0 propan-2-ol

PNEC	140.9 mg/l (sporadic release) 2,251 mg/l (STP) 140.9 mg/l (water (fresh water)) 140.9 mg/l (water (sea water))
PNEC	28 mg/kg (gro) 552 mg/kg (sediment)

##### CAS: 1474044-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters with fatty acids, C18 unsatd., Me sulfates (salts)

PNEC	10 mg/l (STP) 0.017 mg/l (water (fresh water)) 0.002 mg/l (water (sea water))
PNEC	1.7 mg/kg (sediment (fresh water)) 0.17 mg/kg (sediment (sea water)) 0.331 mg/kg (soil)

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 4)

**CAS: 5131-66-8 3-butoxypropan-2-ol**

PNEC	10 mg/l (sewage plant)
	5.25 mg/l (sporadic release)
	0.525 mg/l (water (fresh water))
	0.0525 mg/l (water (sea water))
PNEC	2.36 mg/kg (sediment (fresh water))
	0.236 mg/kg (sediment (sea water))
	0.16 mg/kg (soil)

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls****Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

**Respiratory protection:**

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

**Hand protection**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

[EN 374]

**Penetration time of glove material** Value for the permeation: Level 6 ( $\geq 480$  min)

**Eye/face protection**

Safety glasses

[EN 166]

## SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties****General Information****Physical state**

Fluid

**Colour:**

Red

**Odour:**

Waxen

**Melting point/freezing point:**

Undetermined.

**Boiling point or initial boiling point and boiling range**

82 - 175 °C

**Flammability**

Flammable.

**Lower and upper explosion limit****Lower:**

2 Vol % (CAS: 67-63-0 propan-2-ol)

**Upper:**

13 Vol % (CAS: 67-63-0 propan-2-ol)

**Flash point:**

36 °C (DIN 51755)

**Decomposition temperature:**

Not determined.

**pH at 20 °C**

4.5 - 5.5

**Viscosity:****Kinematic viscosity at 40 °C**

<20.5 mm<sup>2</sup>/s

**Solubility****water:**

Partly miscible.

**Partition coefficient n-octanol/water (log value)**

Not determined.

**Vapour pressure at 20 °C:**

43 hPa (CAS: 67-63-0 propan-2-ol)

**Density and/or relative density****Density at 20 °C:**

0.96 - 0.98 g/cm<sup>3</sup>

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 5)

**Vapour density** Not determined.

**9.2 Other information****Appearance:****Form:**

Fluid

**Important information on protection of health and environment, and on safety.****Ignition temperature:**

Not determined.

**Explosive properties:**

Product does not present an explosion hazard.

**Change in condition****Evaporation rate**

Not determined.

**Information with regard to physical hazard classes****Explosives**

Void

**Flammable gases**

Void

**Aerosols**

Void

**Oxidising gases**

Void

**Gases under pressure**

Void

**Flammable liquids**Sustained combustibility test ISO 9038/UN manual of tests and criteria (32.5.2):  
no self-sustained combustion**Flammable solids**

Void

**Self-reactive substances and mixtures**

Void

**Pyrophoric liquids**

Void

**Pyrophoric solids**

Void

**Self-heating substances and mixtures**

Void

**Substances and mixtures, which emit flammable gases in contact with water**

Void

**Oxidising liquids**

Void

**Oxidising solids**

Void

**Organic peroxides**

Void

**Corrosive to metals**

Void

**Desensitised explosives**

Void

**SECTION 10: Stability and reactivity****10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** See Section 7 for information on safe handling.**10.5 Incompatible materials:** strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****CAS: 67-63-0 propan-2-ol**

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)

**CAS: 1474044-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters with fatty acids, C18 unsatd., Me sulfates (salts)**

Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD TG 402)

**CAS: 9004-78-8 Phenol polyethoxilate**

Oral	LD50	500-2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	2,140 mg/kg (rabbit)

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 6)

**CAS: 5131-66-8 3-butoxypropan-2-ol**

Oral	LD50	3,300 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	>3.5 mg/l (rat) (OECD 403)

**CAS: 71750-79-3 Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me**

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

**CAS: 69011-36-5 isotridecanol,ethoxylated (>5-20EO)**

Oral	LD50	>300-2,000 mg/kg (rat) (OECD 423)
	ATE	>300-2,000 mg/kg (rat)

**CAS: 61791-26-2 Tallow alkylamine ethoxylate**

Oral	LD50	>300-2,000 mg/kg (rat)
------	------	------------------------

**Skin corrosion/irritation** Causes skin irritation.**Serious eye damage/irritation** Causes serious eye damage.**Respiratory or skin sensitisation**

Contains benzyl salicylate. May produce an allergic reaction.  
Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**Additional toxicological information:****Repeated dose toxicity****CAS: 1474044-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters with fatty acids, C18 unsatd., Me sulfates (salts)**

Oral	NOAEL	500 mg/kg (rat) (OECD 407)
Dermal	NOAEL 28d	500 mg/kg (rat) (OECD 407)

**Values relevant for classification:****CAS: 67-63-0 propan-2-ol**

Oral	NOAEL	400 mg/kg/day (rat)
------	-------	---------------------

**11.2 Information on other hazards****Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity**

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

**Aquatic toxicity:****CAS: 67-63-0 propan-2-ol**

LC50 / 96h	9,640 mg/l (Pimephales promelas)
LC50 / 24h	9,714 mg/l (daphnia)
EC50	>100 mg/l (bacteria)
EC50 / 72h	>100 mg/l (algae)
LOEC	1,000 mg/l (algae)

(Contd. on page 8)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 7)

<b>CAS: 1474044-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters withfatty acids, C18 unsatd., Me sulfates (salts)</b>	
LC50 / 96h	>10 mg/l (Cyprinus carpio) (OECD 203)
EC20 / 6d	10 mg/l (activated sludge)
EC50 / 48h	>8.6 mg/l (Daphnia magna) (OECD 202)
EC50 / 72h	1.2 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50 / 6 d	100 mg/l (activated sludge)
NOEC / 21 d	1 mg/l (Daphnia magna) (EPA OTS 797.1330)
NOEC / 72 h	0.39 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC / 35 d	0.686 mg/l (Pimephales promelas) (US-EPA)

<b>CAS: 9004-78-8 Phenol polyethoxilate</b>	
LC50 / 96h	>100 mg/l (fish) (OECD 203)
EC50	>128 mg/kg (Daphnia magna) (OECD 202)

<b>CAS: 5131-66-8 3-butoxypropan-2-ol</b>	
LC50 / 96h	>560-1,000 mg/l (Poecilla reticulata) (OECD 203)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)
EC50 / 48h	>1,000 mg/l (Daphnia magna) (OECD 202)
EC50 / 96 h	>1,000 mg/l (Pseudokirchneriella subcapitata)

<b>CAS: 61791-26-2 Tallow alkylamine ethoxylate</b>	
LC50 / 96 h	0.13 mg/l (Oncorhynchus mykiss)
EC50 / 48h	0.17 mg/l (Daphnia magna)
EC10 / 21 d	>0.001-0.01 mg/l (Daphnia magna)

**12.2 Persistence and degradability**

<b>CAS: 67-63-0 propan-2-ol</b>	
Biodegradation	53 %
<b>CAS: 1474044-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters withfatty acids, C18 unsatd., Me sulfates (salts)</b>	
Biodegradation	>60 % (OECD TG 301 F)
<b>CAS: 9004-78-8 Phenol polyethoxilate</b>	
Biodegradation	>60 % (OECD 311)
<b>CAS: 5131-66-8 3-butoxypropan-2-ol</b>	
Biodegradation	90 % (OECD301E/92/69/EWG, C4.-B)

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:**

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

**vPvB:**

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

**12.6 Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

**12.7 Other adverse effects**

**Additional ecological information:**

**General notes:**

The product does not contain organic complexing agents.

The product may not be released into the environment without control.

The product does not contain organically bounded halogens (AOX-free).

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

GB

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 8)

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

**Recommendation** Waste must be disposed of while observing the local, official regulations.

#### European waste catalogue

07 06 04*	other organic solvents, washing liquids and mother liquors
HP4	Irritant - skin irritation and eye damage
HP14	Ecotoxic

#### Uncleaned packaging:

15 01 10\*: packaging containing residues of or contaminated by dangerous substances

#### Recommendation:

Packaging may be reused or recycled after cleaning.

15 01 02: plastic packaging

**Recommended cleansing agents:** Water

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA Void

#### 14.2 UN proper shipping name

ADR/RID/ADN, IMDG, IATA Void

#### 14.3 Transport hazard class(es)

ADR/RID/ADN, ADN, IMDG, IATA  
Class Void

#### 14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

#### 14.5 Environmental hazards:

**Marine pollutant:** No

#### 14.6 Special precautions for user

Not applicable.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

#### Transport/Additional information:

Sustained combustibility test ISO 9038/UN manual of tests and criteria (32.5.2):  
no self-sustained combustion

#### UN "Model Regulation":

Void

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### European Directives:

Directive 2010/75/EU (VOC) 13.74 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

##### National regulations:

##### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 8.01 (replaces version 8.00)

Revision: 04.05.2023

(Contd. of page 9)

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

### Relevant phrases

H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

### Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation  
Serious eye damage/irritation  
Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Date of previous version:** 21.04.2022

**Version number of previous version:** 8.00

### Abbreviations and acronyms:

NOEL = No Observed Effect Level  
NOEC = No Observed Effect Concentration  
LC = Lethal Concentration  
EC50 = half maximal effective concentration  
log POW = Octanol / water partition coefficient  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
ATE: acute toxicity estimate  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
IOELV = indicative occupational exposure limit values  
Flam. Liq. 2: Flammable liquids – Category 2  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1B: Skin sensitisation – Category 1B  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

\* **Data compared to the previous version altered.**